



**ECOBRITE DES**

**Section: 1. IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING**

**1.1 Product identifier**

Product name : ECOBRITE DES

Product code : 118367E

Use of the Substance/Mixture : Biocide

Substance type: : Mixture

**For professional users only.**

Product dilution information : No dilution information provided.

**1.2 Relevant identified uses of the substance or mixture and uses advised against**

Identified uses : Laundry aid (gasing). Automatic process

Recommended restrictions on use : Reserved for industrial and professional use.

**1.3 Details of the supplier of the safety data sheet**

Company : Ecolab Temizleme Sistemleri Ltd. Şti  
Esentepe Mahallesi, Cevizli - Esentepe E-5 Yanyol Caddesi  
Vizyon Bulvar No: 13, Kat 1 No: 65 Turkey TR 34870 KARTAL / İSTANBUL  
+90 (216) 458 69 00, Fax: +90 (216) 458 69 07

Company : Ecolab Gulf FZE  
P.O. Box 17063  
Jebel Ali Free Zone Area, Near Container Terminal 3 - North Zone, Dubai UAE 00971 4 8014444 Customer Services

Nalco Egypt Trading  
5th Settlement, South 90th St.  
The Address Building No 67th – 1st floor, New Cairo, Cairo, Egypt  
11835  
0020 2 25 37 1195

Ecolab Maroc S.A.R.L.  
Batiment, Lot. Mounir 1, Parc Industriel  
Attawfik, Route 1029 Sidi Maarouf, Casablanca, Morocco 00212  
22 58 25 30 - 35

Company : Ecolab Food Safety & Hygiene Solutions Pvt. Ltd  
WeWork, 247 Park Bus Stop, 13th floor, 247 Park, Hindustan C,  
LBS Road, Gandhi Nagar, Vikhroli West,

**ECOBRITE DES**

Mumbai, Maharashtra. 400 079, India Phone: +91 22 48808555,  
+91 22 48808535 Toll free number: 1800 209 2530

**1.4 Emergency telephone number**

Emergency telephone number : +32-(0)3-575-5555 Trans- European

Poison Information Centre telephone number : 114 Ulusal Zehir Danışma Merkezi (UZEM)

Date of Compilation/Revision : 20.04.2022  
Version : 5.1

**Section: 2. HAZARDS IDENTIFICATION**

**2.1 Classification of the substance or mixture**

**Classification (T.R. SEA No 28848)**

Oxidizing liquids, Category 3	H272
Corrosive to metals, Category 1	H290
Acute toxicity, Category 4	H302
Skin corrosion, Sub-category 1A	H314
Serious eye damage, Category 1	H318
Acute toxicity, Category 4	H332
Specific target organ toxicity - single exposure, Category 3, Respiratory system	H335
Chronic aquatic toxicity, Category 1	H410

The classification of this product is based on toxicological assessment.

**2.2 Label elements**

**Labelling (T.R. SEA No 28848)**

Hazard pictograms :



Signal Word : Danger

Hazard Statements	H272	May intensify fire; oxidiser.
	H290	May be corrosive to metals.
	H302 + H332	Harmful if swallowed or if inhaled.
	H314	Causes severe skin burns and eye damage.
	H335	May cause respiratory irritation.
H410	Very toxic to aquatic life with long lasting effects.	

Supplemental Hazard Statements : EUH071 Corrosive to the respiratory tract.

Precautionary Statements : **Prevention:**  
P210 Keep away from heat, hot surfaces, sparks,

**ECOBRITE DES**

open flames and other ignition sources. No smoking.

P220 Keep away from clothing and other combustible materials.

P261 Avoid breathing vapours.

P280 Wear protective gloves/ eye protection/ face protection.

**Response:**

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER/doctor.

Hazardous components which must be listed on the label:

Hydrogen peroxide

Acetic acid

Peracetic acid

**2.3 Other hazards**

Do not mix with bleach or other chlorinated products – will cause chlorine gas.

**Section: 3. COMPOSITION/INFORMATION ON INGREDIENTS**

**3.2 Mixtures**

**Hazardous components**

Chemical Name	CAS-No. EC-No.	Classification (T.R. SEA No 28848)	Concentration : [%]
Hydrogen peroxide	7722-84-1 231-765-0	Nota B Oxidizing liquids Category 1; H271 Acute toxicity Category 4; H302 Acute toxicity Category 4; H332 Skin corrosion Sub-category 1A; H314 Serious eye damage Category 1; H318 Specific target organ toxicity - single exposure Category 3; H335  Oxidizing liquids Category 1 H271 >= 70 % Oxidizing liquids Category 2 H272 50 - < 70 % Skin corrosion Category 1A H314 >= 70 % Skin corrosion Category 1B H314 50 - < 70 % Skin irritation Category 2 H315 35 - < 50 % Serious eye damage Category 1 H318 8 - < 50 % Eye irritation Category 2 H319 5 - < 8 %	>= 10 - < 20

**ECOBRITE DES**

		Specific target organ toxicity - single exposure Category 3 H335 >= 35 %	
Acetic acid	64-19-7 200-580-7	Nota B Flammable liquids Category 3; H226 Skin corrosion Sub-category 1A; H314 Serious eye damage Category 1; H318  Skin corrosion Category 1A H314 >= 90 % Skin corrosion Category 1B H314 25 - < 90 % Skin irritation Category 2 H315 10 - < 25 % Eye irritation Category 2 H319 10 - < 25 %	>= 10 - < 20
Peracetic acid	79-21-0 201-186-8	Flammable liquids Category 3; H226 Organic peroxides Type D; H242 Acute toxicity Category 4; H302 Acute toxicity Category 4; H332 Acute toxicity Category 4; H312 Skin corrosion Category 1A; H314 Acute aquatic toxicity Category 1; H400 Specific target organ toxicity - single exposure Category 3; H335 Chronic aquatic toxicity Category 1; H410  Specific target organ toxicity - single exposure Category 3 H335 >= 1 % M = 1 M(Chronic) = 10	>= 10 - < 20
octanoic acid	124-07-2 204-677-5	Skin corrosion Category 1C; H314 Serious eye damage Category 1; H318 Chronic aquatic toxicity Category 3; H412  Skin corrosion/irritation Category 1C > 70 - 100 %	>= 2.5 - < 3
Sulfonic acids, C14-17-sec-alkane, sodium salts	97489-15-1 307-055-2	Acute toxicity Category 4; H302 Skin irritation Category 2; H315 Serious eye damage Category 1; H318 Chronic aquatic toxicity Category 3; H412  Serious eye damage/eye irritation Category 1 > 15 - 100 % Serious eye damage/eye irritation Category 2A > 10 - 15 %	>= 1 - < 2.5
Peroxyoctanoic acid	33734-57-5	Pyrophoric liquids Category 1; H250 Organic peroxides Type F; H242 Skin corrosion Category 1B; H314 Serious eye damage Category 1; H318 Acute aquatic toxicity Category 1; H400	>= 1 - < 2.5
Substances with a workplace exposure limit :			

**ECOBRITE DES**

<p>sulphuric acid</p>	<p>7664-93-9 231-639-5</p>	<p>Nota B Skin corrosion Category 1A; H314  Skin corrosion Category 1A H314 &gt;= 15 % Skin irritation Category 2 H315 5 - &lt; 15 % Eye irritation Category 2 H319 5 - &lt; 15 %</p>	<p>&gt;= 0.25 - &lt; 0.5</p>
-----------------------	--------------------------------	---	----------------------------------

For the full text of the H-Statements mentioned in this Section, see Section 16.

**Section: 4. FIRST AID MEASURES**

**4.1 Description of first aid measures**

- In case of eye contact : Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention immediately.
- In case of skin contact : Wash off immediately with plenty of water for at least 15 minutes. Wash clothing before reuse. Thoroughly clean shoes before reuse. Get medical attention immediately.
- If swallowed : Rinse mouth with water. Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Get medical attention immediately.
- If inhaled : Remove to fresh air. Treat symptomatically. Get medical attention.

**4.2 Most important symptoms and effects, both acute and delayed**

See Section 11 for more detailed information on health effects and symptoms.

**4.3 Indication of immediate medical attention and special treatment needed**

- Treatment : Treat symptomatically.

**Section: 5. FIREFIGHTING MEASURES**

**5.1 Extinguishing media**

- Suitable extinguishing media : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
- Unsuitable extinguishing media : Anything other than water

**5.2 Special hazards arising from the substance or mixture**

- Specific hazards during firefighting : Special protective equipment for firefighters  
Oxidizer. Contact with other material may cause fire.  
On decomposition, releases oxygen which may intensify fire.  
Oxidizer; material is an oxidizer which may readily react with other materials, especially upon heating.  
Risk of over-pressure and bursting in the event of decomposition in closed containers.

**ECOBRITE DES**

In case of a fire, if it is possible without risk, remove all containers exposed to the fire and store them in a safe place, away from any source of heat.

Cool closed containers exposed to fire with water spray.

Hazardous combustion products : Depending on combustion properties, decomposition products may include following materials:  
Carbon oxides  
Sulphur oxides  
metal oxides

**5.3 Advice for firefighters**

Special protective equipment for firefighters : In case of fire, wear a full face positive-pressure self contained breathing apparatus and protective suit.

Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. In the event of fire and/or explosion do not breathe fumes.

**Section: 6. ACCIDENTAL RELEASE MEASURES**

**6.1 Personal precautions, protective equipment and emergency procedures**

Advice for non-emergency personnel : Ensure adequate ventilation. Eliminate any possible source of ignition. Keep people away from and upwind of spill/leak. Avoid inhalation, ingestion and contact with skin and eyes. When workers are facing concentrations above the exposure limit they must use appropriate certified respirators. Ensure clean-up is conducted by trained personnel only. Move all flammable sources out of danger and keep them away from the scene. Refer to protective measures listed in sections 7 and 8.

Advice for emergency responders : If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials.

**6.2 Environmental precautions**

Environmental precautions : Do not allow contact with soil, surface or ground water. DO NOT hermetically seal any defective containers, including drums (risk of bursting due to the decomposition of the product)

**6.3 Methods and materials for containment and cleaning up**

Methods for cleaning up : Stop leak if safe to do so. Isolate the waste do not allow it to come into contact with incompatible materials. For small spills contain with sand or vermiculite and dilute the contained product at least 10 times with water. Transfer to an open topped container and remove to a safe place for neutralization\* / disposal. For large spills contain spill and evacuate the area, leave until the reaction subsides, then collect up for disposal. Obtain consent from the local water company / authority if considering discharge to sewer.  
\*NEUTRALIZATION : once diluted, neutralize with a suitable alkali

## **ECOBRITE DES**

such as sodium bicarbonate. Combustible materials exposed to this product should be rinsed immediately with large amounts of water to ensure that all product is removed. Residual product which is allowed to dry on organic materials such as rags, cloths, paper, fabrics, cotton, leather, wood, or other combustibles may spontaneously ignite and result in a fire.

### **6.4 Reference to other sections**

See Section 1 for emergency contact information.  
For personal protection see section 8.  
See Section 13 for additional waste treatment information.

## **Section: 7. HANDLING AND STORAGE**

### **7.1 Precautions for safe handling**

- Advice on safe handling : Do not ingest. Do not get in eyes, on skin, or on clothing. Use only with adequate ventilation. Wash hands thoroughly after handling. Do not breathe spray, vapour. Do not mix with bleach or other chlorinated products – will cause chlorine gas. In case of mechanical malfunction, or if in contact with unknown dilution of product, wear full Personal Protective Equipment (PPE).
- Hygiene measures : Handle in accordance with good industrial hygiene and safety practice. Remove and wash contaminated clothing before re-use. Wash face, hands and any exposed skin thoroughly after handling. Provide suitable facilities for quick drenching or flushing of the eyes and body in case of contact or splash hazard.

### **7.2 Conditions for safe storage, including any incompatibilities**

- Requirements for storage areas and containers : Keep away from reducing agents. Keep away from combustible material. Absorb spillage to prevent material damage. Keep out of reach of children. Keep container tightly closed. Store in suitable labeled containers. Pressure bursts may occur due to gas evolution if the container is not adequately vented. Keep in the original container only, in a cool and well-ventilated place, out of the light and away from combustible materials and reducing agents (amines), acids, bases, heavy metal compounds (accelerators, siccative agents, metallic salts). Store on an acid-resistant floor. Do not hermetically seal the container. Always transport and store the containers upright. Risk of overpressure and bursting in the event of decomposition in closed containers and in pipes.
- Storage temperature : -5 °C to 30 °C
- Packaging material : Suitable material: Plastic material  
Unsuitable material: Mild steel, Aluminium

### **7.3 Specific end uses**

- Specific use(s) : Laundry aid (gasing). Automatic process

**ECOBRITE DES**

**Section: 8. EXPOSURE CONTROLS/PERSONAL PROTECTION**

**8.1 Control parameters**

**Occupational Exposure Limits**

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
Acetic acid	64-19-7	TWA (8 Hour)	10 ppm 25 mg/m3	TR OEL
		TWA	10 ppm 25 mg/m3	2017/164/EU
Further information		Indicative		
		STEL	20 ppm 50 mg/m3	2017/164/EU
Further information		Indicative		
Acetic acid	64-19-7	TWA	10 ppm 25 mg/m3	ARE OEL
		STEL	15 ppm 37 mg/m3	ARE OEL
Acetic acid	64-19-7	TWA	10 ppm 25 mg/m3	IN OEL
		STEL	15 ppm 37 mg/m3	IN OEL
sulphuric acid	7664-93-9	TWA (8 Hour)	1 mg/m3	TR OEL
		TWA (8 Hour) (Mist)	0.05 mg/m3	TR OEL
sulphuric acid	7664-93-9	TWA (Measured as thoracic fraction of the aerosol)	0.2 mg/m3	ARE OEL
Further information	A2	Suspected Human Carcinogen		
	(M)	Classification refers to sulfuric acid contained in strong inorganic acid mists.		
sulphuric acid	7664-93-9	TWA	1 mg/m3	IN OEL

**DNEL**

Peracetic acid	:	<p>End Use: Workers Exposure routes: Inhalation Potential health effects: Long-term systemic effects Value: 0.56 mg/m3</p> <p>End Use: Workers Exposure routes: Inhalation Potential health effects: Acute systemic effects Value: 0.56 mg/m3</p> <p>End Use: Workers Exposure routes: Inhalation Potential health effects: Long-term local effects Value: 0.56 mg/m3</p> <p>End Use: Workers Exposure routes: Inhalation Potential health effects: Acute local effects Value: 0.56 mg/m3</p> <p>End Use: Consumers Exposure routes: Inhalation</p>
----------------	---	---



**ECOBRITE DES**

	<p>Potential health effects: Long-term systemic effects Value: 0.28 mg/m3</p> <p>End Use: Consumers Exposure routes: Inhalation Potential health effects: Acute systemic effects Value: 0.28 mg/m3</p> <p>End Use: Consumers Exposure routes: Inhalation Potential health effects: Long-term local effects Value: 0.28 mg/m3</p> <p>End Use: Consumers Exposure routes: Inhalation Potential health effects: Acute local effects Value: 0.28 mg/m3</p> <p>End Use: Consumers Exposure routes: Oral Potential health effects: Long-term systemic effects Value: 1.25 mg/m3</p> <p>End Use: Consumers Exposure routes: Oral Potential health effects: Acute systemic effects Value: 1.25 mg/m3</p>
--	--

**PNEC**

Peracetic acid	<p>: Fresh water Value: 0.000224 mg/l</p> <p>Fresh water sediment Value: 0.00018 mg/kg</p> <p>Water Value: 0.051 mg/l</p> <p>Soil Value: 0.32 mg/kg</p>
----------------	---

**8.2 Exposure controls**

**Appropriate engineering controls**

Engineering measures : Effective exhaust ventilation system. Maintain air concentrations below occupational exposure standards.

**Individual protection measures**

Hygiene measures : Handle in accordance with good industrial hygiene and safety practice. Remove and wash contaminated clothing before re-use.

## ECOBRITE DES

Wash face, hands and any exposed skin thoroughly after handling. Provide suitable facilities for quick drenching or flushing of the eyes and body in case of contact or splash hazard.

- Eye/face protection (EN 166) : Safety goggles  
Face-shield
- Hand protection (EN 374) : In case of skin contact it is recommended to wear gloves to avoid oxidation effect (e.g. skin whitening)  
Recommended preventive skin protection  
Gloves  
Nitrile rubber  
butyl-rubber  
Breakthrough time: 1 – 4 hours  
Minimum thickness for butyl-rubber 0.7 mm for nitrile rubber 0.4 mm or equivalent (please refer to the gloves manufacturer/distributor for advise).  
Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough.
- Skin and body protection (EN 14605) : Personal protective equipment comprising: suitable protective gloves, safety goggles and protective clothing including appropriate safety shoes
- Respiratory protection (EN 143, 14387) : When respiratory risks cannot be avoided or sufficiently limited by technical means of collective protection or by measures, methods or procedures of work organization, consider the use of certified respiratory protection equipment meeting EU requirements (89/656/EEC, (EU) 2016/425), or equivalent, with filter type:A-P

### Environmental exposure controls

- General advice : Consider the provision of containment around storage vessels.

## Section: 9. PHYSICAL AND CHEMICAL PROPERTIES

### 9.1 Information on basic physical and chemical properties

- Appearance : liquid
- Colour : clear, colourless
- Odour : vinegar-like
- pH : 2.5 - 3.5, 1 %
- Flash point : Not applicable.
- Odour Threshold : Not applicable and/or not determined for the mixture
- Melting point/freezing point : Not applicable and/or not determined for the mixture
- Initial boiling point and boiling range : Not applicable and/or not determined for the mixture
- Evaporation rate : Not applicable and/or not determined for the mixture
- Flammability (solid, gas) : Not applicable and/or not determined for the mixture

**ECOBRITE DES**

Upper explosion limit	: Not applicable and/or not determined for the mixture
Lower explosion limit	: Not applicable and/or not determined for the mixture
Vapour pressure	: Not applicable and/or not determined for the mixture
Relative vapour density	: Not applicable and/or not determined for the mixture
Relative density	: 1.1 - 1.15
Water solubility	: soluble
Solubility in other solvents	: Not applicable and/or not determined for the mixture
Partition coefficient: n-octanol/water	: Not applicable and/or not determined for the mixture
Auto-ignition temperature	: Not applicable and/or not determined for the mixture
Thermal decomposition	: Not applicable and/or not determined for the mixture
Viscosity, kinematic	: Not applicable and/or not determined for the mixture
Explosive properties	: Not applicable and/or not determined for the mixture
Oxidizing properties	: Yes

**9.2 Other information**

Not applicable and/or not determined for the mixture

**Section: 10. STABILITY AND REACTIVITY**

**10.1 Reactivity**

Stable under normal conditions of use.  
Decomposes on heating. Potential for exothermic hazard.

**10.2 Chemical stability**

Decomposes on heating.  
Decomposes on exposure to light.  
Contamination may result in dangerous pressure increases - closed containers may rupture.

**10.3 Possibility of hazardous reactions**

Decomposes on exposure to light.  
Do not mix with bleach or other chlorinated products – will cause chlorine gas.  
Avoid amines.

**10.4 Conditions to avoid**

Heat.  
Direct sources of heat.  
Exposure to sunlight.  
Exposure to light.  
Freezing temperatures.

**10.5 Incompatible materials**

Mild steel

**ECOBRITE DES**

Aluminium  
Acids  
Bases  
Powdered metal salts  
Metals  
Reducing agents  
Flammable materials  
Organic materials  
Heavy metal salts

**10.6 Hazardous decomposition products**

Depending on combustion properties, decomposition products may include following materials:  
Carbon oxides  
Sulphur oxides  
metal oxides

**Section: 11. TOXICOLOGICAL INFORMATION**

**11.1 Information on toxicological effects**

Information on likely routes of exposure : Inhalation, Eye contact, Skin contact

**Product**

Acute oral toxicity : Acute toxicity estimate : 1,520 mg/kg  
Acute inhalation toxicity : Harmful if inhaled. :  
Acute dermal toxicity : Acute toxicity estimate : > 2,000 mg/kg  
Skin corrosion/irritation : There is no data available for this product.  
Serious eye damage/eye irritation : There is no data available for this product.  
Respiratory or skin sensitization : There is no data available for this product.  
Carcinogenicity : There is no data available for this product.  
Reproductive effects : There is no data available for this product.  
Germ cell mutagenicity : There is no data available for this product.  
Teratogenicity : There is no data available for this product.  
STOT - single exposure : There is no data available for this product.  
STOT - repeated exposure : There is no data available for this product.  
Aspiration toxicity : There is no data available for this product.

## **ECOBRITE DES**

### **Components**

Acute oral toxicity : Hydrogen peroxide LD50 rat: 486 mg/kg  
Acetic acid LD50 rat: 3,310 mg/kg  
octanoic acid LD50 rat: > 2,000 mg/kg  
Sulfonic acids, C14-17-sec-alkane, sodium salts LD50 rat: 1,250 mg/kg  
Peroxyoctanoic acid LD50 rat: > 2,000 mg/kg

### **Components**

Acute inhalation toxicity : Hydrogen peroxide 4 h LC50 rat: 11 mg/l  
Test atmosphere: vapour  
Peracetic acid 4 h LC50 rat: 1.5 mg/l  
Test atmosphere: dust/mist

### **Components**

Acute dermal toxicity : Acetic acid LD50 rabbit: 1,060 mg/kg  
Sulfonic acids, C14-17-sec-alkane, sodium salts LD50 mouse: > 2,000 mg/kg

### **Potential Health Effects**

Eyes : Causes serious eye damage.  
Skin : Causes severe skin burns.  
Ingestion : Causes digestive tract burns.  
Inhalation : May cause nose, throat, and lung irritation.  
Chronic Exposure : Health injuries are not known or expected under normal use.

### **Experience with human exposure**

Eye contact : Redness, Pain, Corrosion  
Skin contact : Redness, Pain, Corrosion  
Ingestion : Corrosion, Abdominal pain  
Inhalation : Respiratory irritation, Cough

## **Section: 12. ECOLOGICAL INFORMATION**

### **12.1 Toxicity**

Environmental Effects : Very toxic to aquatic life with long lasting effects.

## ECOBRITE DES

### Product

Toxicity to fish : no data available

Toxicity to daphnia and other aquatic invertebrates : no data available

Toxicity to algae : no data available

### Components

Toxicity to fish : Hydrogen peroxide 96 h LC50 Pimephales promelas (fathead minnow): 16.4 mg/l

Acetic acid 96 h LC50 Oncorhynchus mykiss (rainbow trout): > 1,000 mg/l

Peracetic acid 96 h LC50: 0.8 mg/l

octanoic acid 96 h LC50 Lepomis macrochirus (Bluegill sunfish): 22 mg/l

Sulfonic acids, C14-17-sec-alkane, sodium salts 96 h LC50 Leuciscus idus (Golden orfe): 8.4 mg/l

Peroxyoctanoic acid 96 h LC50 Fish: 0.15 mg/l

sulphuric acid 96 h LC50: 22 mg/l

### Components

Toxicity to daphnia and other aquatic invertebrates : Hydrogen peroxide 48 h LC50 Daphnia magna (Water flea): 2.4 mg/l

Acetic acid 48 h EC50 Daphnia magna (Water flea): 39.6 mg/l

Peracetic acid 48 h EC50: 0.73 mg/l

Sulfonic acids, C14-17-sec-alkane, sodium salts 48 h EC50 Daphnia magna (Water flea): 9.2 mg/l

### Components

Toxicity to algae : Hydrogen peroxide 72 h EC50 Skeletonema costatum (marine diatom): 1.38 mg/l

Acetic acid 72 h EC50 Skeletonema costatum (marine diatom): > 1,000 mg/l

Peracetic acid 72 h EC50: 0.7 mg/l

## 12.2 Persistence and degradability

### Product

no data available

### Components

## ECOBRITE DES

Biodegradability : Hydrogen peroxideResult: Not applicable - inorganic  
Acetic acidResult: Readily biodegradable.  
Peracetic acidResult: Readily biodegradable.  
octanoic acidResult: Readily biodegradable.  
Sulfonic acids, C14-17-sec-alkane, sodium saltsResult: Readily biodegradable.  
Peroxyoctanoic acidResult: Readily biodegradable.  
sulphuric acidResult: Not applicable - inorganic

### 12.3 Bioaccumulative potential

no data available

### 12.4 Mobility in soil

no data available

### 12.5 Results of PBT and vPvB assessment

#### Product

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

### 12.6 Other adverse effects

no data available

## Section: 13. DISPOSAL CONSIDERATIONS

Dispose of in accordance with the European Directives on waste and hazardous waste. Waste codes should be assigned by the user, preferably in discussion with the waste disposal authorities.

### 13.1 Waste treatment methods

Product : Do not contaminate storm water drains, natural waterways or soil with chemical or used container. Where possible recycling is preferred to disposal or incineration. If recycling is not practicable, dispose of contents/container in accordance with local regulations  
Dispose of wastes in an approved waste disposal facility.

Contaminated packaging : Dispose of as unused product. Empty containers should be taken to an approved waste handling site for recycling or disposal. Do not re-use empty containers. Dispose of in accordance with local, state, and federal regulations.

Guidance for Waste Code : Organic wastes containing dangerous substances. If this product

**ECOBRITE DES**

selection is used in any further processes, the final user must redefine and assign the most appropriate European Waste Catalogue Code. It is the responsibility of the waste generator to determine the toxicity and physical properties of the material generated to determine the proper waste identification and disposal methods in compliance with applicable European (EU Directive 2008/98/EC) and local regulations.

**Section: 14. TRANSPORT INFORMATION**

The shipper/consignor/sender is responsible to ensure that the packaging, labeling, and markings are in compliance with the selected mode of transport.

**Land transport (ADR/ADN/RID)**

14.1 UN number : 3098  
14.2 UN proper shipping name : OXIDIZING LIQUID, CORROSIVE, N.O.S.  
(Hydrogen peroxide, Peroxyacetic acid, acetic acid)  
14.3 Transport hazard class(es) : 5.1 (8)  
14.4 Packing group : III  
14.5 Environmental hazards : Yes  
14.6 Special precautions for user : None

**Air transport (IATA)**

14.1 UN number : 3098  
14.2 UN proper shipping name : Oxidizing liquid, corrosive, n.o.s.  
(Hydrogen peroxide, Peroxyacetic acid, acetic acid)  
14.3 Transport hazard class(es) : 5.1 (8)  
14.4 Packing group : III  
14.5 Environmental hazards : Yes  
14.6 Special precautions for user : None

**Sea transport (IMDG/IMO)**

14.1 UN number : 3098  
14.2 UN proper shipping name : OXIDIZING LIQUID, CORROSIVE, N.O.S.  
(Hydrogen peroxide, Peroxyacetic acid, acetic acid)  
14.3 Transport hazard class(es) : 5.1 (8)  
14.4 Packing group : III  
14.5 Environmental hazards : Yes  
14.6 Special precautions for user : None  
14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC : Not applicable.



**ECOBRITE DES**

Code

**Section: 15. REGULATORY INFORMATION**

**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

according to Detergents Regulation EC 648/2004 : 15 % or over but less than 30 %: Oxygen-based bleaching agents  
Contains: Disinfectants

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances. : ENVIRONMENTAL HAZARDS E1  
Lower tier : 100 t  
Upper tier : 200 t  
OXIDIZING LIQUIDS AND SOLIDS P8  
Lower tier : 50 t  
Upper tier : 200 t

**National Regulations**

**Take note of Dir 94/33/EC on the protection of young people at work.**

Other regulations : According to 11 December 2013, Numbered 28848 (Bis), "Ministry of Environment and Forestry"; Regulation on Classification, Labelling and Packaging of Substances and Mixtures.  
According to 13 Dec 2014, Numbered 29204, "Ministry of Environment and Urbanization"; Regulation on Safety Data Sheets regarding Dangerous Substances and Mixtures.

**15.2 Chemical Safety Assessment**

No Chemical Safety Assessment has been carried out on the product.

**Section: 16. OTHER INFORMATION**

**Procedure used to derive the classification according to REGULATION (EC) No 1272/2008 and Regulation T.R. SEA No 28848**

<b>Classification</b>	<b>Justification</b>
Oxidizing liquids 3, H272	Expert judgement and weight of evidence determination.
Corrosive to metals 1, H290	Expert judgement and weight of evidence determination.
Acute toxicity 4, H302	Calculation method
Skin corrosion 1A, H314	Calculation method
Serious eye damage 1, H318	Calculation method
Acute toxicity 4, H332	Expert judgement and weight of evidence determination.
Specific target organ toxicity - single exposure 3, H335	Calculation method
Chronic aquatic toxicity 1, H410	Calculation method

**Full text of H-Statements**

**ECOBRITE DES**

H226	Flammable liquid and vapour.
H242	Heating may cause a fire.
H250	Catches fire spontaneously if exposed to air.
H271	May cause fire or explosion; strong oxidiser.
H302	Harmful if swallowed.
H312	Harmful in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H318	Causes serious eye damage.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

**Full text of other abbreviations**

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road; AIIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TECl - Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

Prepared by : Name, Surname: Betül Sevim  
Certificate number: LONCA KDU 98 / 2022. 06  
Certificate date: 05.02.2022  
Certificate expiry date: 05.02.2027  
Contact: +90 216 458 6962

**ECOBRITE DES**

Numbers quoted in the MSDS are given in the format: 1,000,000 = 1 million and 1,000 = 1 thousand. 0.1 = 1 tenth and 0.001 = 1 thousandth

REVISED INFORMATION: Significant changes to regulatory or health information for this revision is indicated by a bar in the left-hand margin of the SDS.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.